

SK _____

NEVYHNUTNOSŤ:

- **Grafika max. do 8 farieb vrátane bielej.**
- **Potrebueme tlačové PDF zmontované v programe Adobe Illustrator (CS4 až CC)**
- **Obrázky použité v grafike poslat' samostatne ako vrstvové PSD v rozlíšení minimálne 300 dpi**
- **Všetky texty rozbite na krvky (alebo dodat' použité fontové sady)**
- **Vždy priložiť kontrolne náhľadové PDF**

ZÁKLADNÉ POŽIADAVKY:

- **transparentný obal** - ak nemá byť obal celoplošne podkrytý bielou **dodat' vo vektorovom tlačovovom PDF vrstvu bielej farby pre každý objekt** ktorý ma byť podkrytý (aby nebol priesvitný)
- **minimálna hrúbka pozitívnej linky** 0,1 mm
- **minimálna hrúbka negatívnej linky** 0.15mm
- **minimálna hrúbka pozitívneho textu 4 body** (minimálny pozitívny text musí byť zložený len z jednej farby) pozitívne texty len z jednej farby
- **minimálna hrúbka negatívneho textu 5 bodov** (minimálny negatívny text musí byť zložený len z jednej farby) negatívne texty len z jednej farby
- **minimálna výška textu podla legislatívy EU je 1.3 mm**
- **minimálny bod v dátach 1%** (prosim pamäťajte na NÁRAST TLAČOVÉHO BODU **vytlačený bod** na vzorke má približne **7%**)
- **maximálny vytlačiteľný bod 300%** (vytlačený bod na vzorke (300%) - 3 farby cez seba
- **minimálna veľkosť EAN-u = 80% normalizovanej veľkosti (30mm)**

UK _____

ESSENTIALS

- **Artwork up to 8 colours including white**
- **We need print PDF prepared in Adobe Illustrator (CS 4 up to CC)**
- **Please attach used images in the artwork as separate PSD files in layers**
- **All texts must be in curves (or attach used text fonts)**
- **Always attach preview PDF**

BASIC REQUIREMENTS

- Transparent package-if the whole package is not going to be under printed by white, please attach in print PDF one layer for white colour for every objects which needs to be covered (to avoid its transparency)
- minimum size of positive line 0.1 mm
- minimum size of negative line 0.15 mm
- minimum size of positive texts 4 pt (minimum size of positive texts must contain one colour only!) /positive texts in one colour only

- minimum size of negative texts 5 pt (minimum size of negative texts must contain one colour only!) /negatoive texts in one colour only
- please note all texts in EU must be 1.3 mm high.
- minimum size of dot in data 1% (please note DOT GAIN -this dot has on printing sample approximately 7%)
- maximum in data 300% (on printing sample 300%) - layer of three colours
- minimum size of BAR CODE is 80% of normalized size (30mm)